

SOX Product Specifications

Anchoring Stake Examples:

(CSP to determine stakes used based on substrate)

1. Earthen & Sandy Deployments (ex. Golf Courses)
 - Untreated Wooden Stakes
 - 100% Biodegradable
 - 2" x 2" with lengths of 2' or longer
2. Stone, Rock, Shale or Solid Substrates
 - Rigid metal anchor based upon environment
3. Concrete Embankments or other man-made hardened substrates
 - Galvanized, Stainless or other Metal Eyehooks

Draw Cord & Anchor Rope

- Anchor Rope: 1/4" Diamond Braid



950 Peninsula Corporate Circle
 Suite 2020
 Boca Raton, Florida 33487
 Office: 561-501-0057
office@soxerosion.com
www.soxerosion.com

MSDS Available upon request.

DredgeSOX Specs :

	Composition	Break Strength Grab Method ASTM-D5034	Break Elongation Grab Method ASTM-5034	Tear Strength Trapezoid ASTM-D5587, #1	Bursting Strength ASTM-D3786
SOX Mesh Type II	Tape / Tape	Warp: 135 lbs	Warp: 32.33%	Warp: 58.0 lbs	284 psi
		Fill: 207 lbs	Fill: 61.7%	Fill: 70.3 lbs	